

```
-----/etc/phpmyadmin# vi apache.conf -----
```

```
Alias /phpmyadmin /usr/share/phpmyadmin
```

```
<Directory /usr/share/phpmyadmin>
```

```
Options FollowSymLinks
```

```
DirectoryIndex index.php
```

```
<IfModule mod_php5.c>
```

```
AddType application/x-httpd-php .php
```

```
php_flag magic_quotes_gpc Off
```

```
php_flag track_vars On
```

```
php_flag register_globals Off
```

```
php_value include_path .
```

```
</IfModule>
```

```
#Allowing remote access to PHPMyAdmin
```

```
Order Deny,Allow
```

```
Deny from All
```

```
#Allow from All
```

```
Allow from 210.4.64.0/24 180.211.136.0/24 103.204.211.181/32
```

```
</Directory>
```

```
-----  
/etc/phpmyadmin
```

```
root@apps:/etc/phpmyadmin# vi config.inc.php
```

```
//$cfg['Servers'][$i]['AllowRoot'] = TRUE; // whether to allow root login
```

```
$cfg['Servers'][$i]['AllowRoot'] = FALSE; // whether to allow root login
```

In `/etc/phpmyadmin/config.inc.php`, look for the following line and make sure the `AllowRoot` directive is set to FALSE:

```
Scfg['Servers'][$i]['AllowRoot'] = FALSE;
```

```
61 /* Configure according to dbconfig-common if enabled */
62 if (!empty($dbname)) {
63     /* Authentication type */
64     $cfg['Servers'][$i]['auth_type'] = 'cookie';
65     $cfg['Servers'][$i]['AllowRoot'] = FALSE;
66     /* Server parameters */
67     if (empty($dbserver)) $dbserver = 'localhost';
68     $cfg['Servers'][$i]['host'] = $dbserver;
69
```

Disable Root Login in PhpMyAdmin

In Ubuntu/Debian, you need to add these two lines as shown:

```
/* Authentication type */
Scfg['Servers'][$i]['auth_type'] = 'cookie';
Scfg['Servers'][$i]['AllowRoot'] = false;
```

Save changes and restart Apache.

```
=====  
=====apache Document apache soft file create =====command  
In -s webmail www_ebmail [ Document root name ]
```

```
=====  
mysql -p phpmyadmin < create_tables.sql
```

```
14th##=====14th apache2.conf =====
```

```
vi /etc/apache2/apache2.conf
```

```
KeepAlive Off
```

```
HostnameLookups Off
```

```
-----  
vi /etc/apache2/ports.conf
```

```
Listen 80
```

```
-----  
ls conf-enabled/
```

```
vi conf-enabled//security.conf
```

```
ServerTokens Prod
```

```
ServerSignature Off
```

```
TraceEnable Off
```

```
apache2-doc.conf    localized-error-pages.conf    security.conf
```

```
charset.conf      other-vhosts-access-log.conf  serve-cgi-bin.conf
javascript-common.conf  phpmyadmin.conf
```

```
a2disconf serve-cgi-bin
a2disconf apache2-doc
ls conf-available/
apache2-doc.conf    localized-error-pages.conf  security.conf
charset.conf        other-vhosts-access-log.conf  serve-cgi-bin.conf
javascript-common.conf  phpmyadmin.conf
```

```
vi conf-available/security.conf
ServerTokens Prod
ServerSignature Off
TraceEnable Off
```

```
ls mods-enabled/
vi mods-available/mpm_prefork.conf
<IfModule mpm_prefork_module>
    StartServers      2
    MinSpareServers   5
    MaxSpareServers   10
    ServerLimit       210
    MaxRequestWorkers 200
    MaxConnectionsPerChild 100
</IfModule>
```

```
vi mods-available/env.load
LoadModule env_module /usr/lib/apache2/modules/mod_env.so
apache2ctl -M
a2enmod rewrite
a2enmod headers
```

15th=====15th ini.php=====

```
vi /etc/php5/apache2/php.ini
vi php.ini
```

```
----- default-----
;disable_functions =
pcntl_alarm,pcntl_fork,pcntl_waitpid,pcntl_wait,pcntl_wifexited,pcntl_wifstopped,pcntl_wifsignaled,pcntl_wexitsig,pcntl_wtermsig,pcntl_wstopsig,pcntl_signal,pcntl_signal_dispatch,pcntl_get_last_error,pcntl_strerror,pcntl_sigprocmask,pcntl_sigwaitinfo,pcntl_sigtimedwait,pcntl_exec,pcntl_getpriority,pcntl_setpriority,
```

disable_functions = _getppid, apache_child_terminate, apache_get_modules,
apache_get_version, apache_getenv, apache_note, apache_setenv, cat, cd, chgrp, chmod,
chown, cmd, cp, dbase_open, dbmopen, define_syslog_variables, delete, deleted,
diskfreespace, dl, edit, escapeshellarg, escapeshellcmd, eval, exec, file_upload, fp, fpassthru,
fpaththru, fput, ftp_alloc, ftp_cdup, ftp_chdir, ftp_chmod, ftp_close, ftp_connect, ftp_delete,
ftp_exec, ftp_fget, ftp_fput, ftp_get, ftp_get_option, ftp_login, ftp_mdtm, ftp_mkdir,
ftp_nb_continue, ftp_nb_fget, ftp_nb_fput, ftp_nb_get, ftp_nb_put, ftp_nlist, ftp_pasv, ftp_put,
ftp_pwd, ftp_quit, ftp_raw, ftp_rawlist, ftp_rename, ftp_rmdir, ftp_set_option, ftp_site, ftp_size,
ftp_ssl_connect, ftp_systyp, get_current_user, getenv, getmypid, getmyuid, gzinflate,
highlight_file, ignore_user_abort, ini_alter, ini_get_all, ini_restore, ini_set, inject_code, leak,
link, listen, ln, mv, mysql_get_client_info, mysql_list_dbs, openlog, parse_ini_file, parse_perms,
passthru, pclose, pcntl_alarm, pcntl_exec, pcntl_fork, pcntl_get_last_error, pcntl_getpriority,
pcntl_setpriority, pcntl_signal, pcntl_signal_dispatch, pcntl_sigprocmask, pcntl_sigtimedwait,
pcntl_sigwaitinfo, pcntl_strerror, pcntl_wait, pcntl_waitpid, pcntl_wexitstatus, pcntl_wifexited,
pcntl_wifsignaled, pcntl_wifstopped, pcntl_wstopid, pcntl_wtermsig, pconnect, pfsckopen,
pg_lo_import, phpAds_XmlRpc, phpAds_remoteInfo, phpAds_xmlrpcDecode,
phpAds_xmlrpcEncode, php_uname, pico, popen, posix, posix_ctermid, posix_getcwd,
posix_getegid, posix_geteuid, posix_getgid, posix_getgrgid, posix_getgrnam, posix_getgroups,
posix_getlogin, posix_getpgid, posix_getpgrp, posix_getpid, posix_getpwnam, posix_getpwuid,
posix_getrlimit, posix_getsid, posix_getuid, posix_isatty, posix_kill, posix_mkfifo, posix_setegid,
posix seteuid, posix_setgid, posix_setpgid, posix_setsid, posix_setuid, posix_times,
posix_ttyname, posix_uname, proc_close, proc_get_status, proc_nice, proc_open,
proc_terminate, rename, shell_exec, show_source, socket_accept, socket_bind,
socket_clear_error, socket_close, socket_connect, socket_create, socket_create_listen,
socket_create_pair, socket_listen, socket_select, socket_strerror, source, stream_select,
symlink, syslog, system, tmpfile, touch, virtual, xmlrpc_entity_decode, phpinfo

max_execution_time = 360
max_input_time = 120
display_errors = On
ignore_repeated_errors = On
post_max_size = 16M
 upload_max_filesize = 10M
max_file_uploads = 10

=====